

# SONALIKA

## HEAVY DUTY TRACTOR RANGE FOR YOUR FIELD

# 125



AGILE 6 CYLINDER  
ENGINE

24F+24R SYNCHROMESH  
TRANSMISSION

HEAVY LIFT  
CAPACITY

SMART TECH  
FEATURES

INTEGRATED SAFETY  
HVAC CABIN (OPTIONAL)



**COST  
EFFICIENT**  
MECHANICAL TRACTORS

MADE OF  
**REAL  
STEEL**

STRATEGIC  
COLLABORATION  
WITH  
**YANMAR**

# HEAVY DUTY TRACTOR RANGE FOR YOUR FIELD

## 125

# SONALIKA



FEATURES		Sonalika 125 HP CABIN
<b>ENGINE</b>		
HP Category		125 HP
No. of Cylinders		6
Displacement cc		6.127 L
Aspiration		Turbocharged with Intercooler
Bore/Stroke (mm)		105 x 118
Rated RPM		2200
Air Cleaner		Three stage dry type
Max Torque		475
<b>TRANSMISSION</b>		
Drive		4WD
Clutch		Double Clutch
Gearbox		24+24
Transmission		Synchromesh Gear Box
4WD Engagement		Electrical Switch Operated
<b>SPEED (FORWARD)</b>		
Min Speed (km/h)		0.67 Kmph
Max Speed (km/h)		40 Kmph
Driver Seat		Mechanical Suspension
<b>BRAKES</b>		
Brakes		Wet Disk Brakes
Type of Actuation		Hydraulic Actuated
Hand Brake		Mechanical, Hand operated
Trailer Brakes		HTB (Standard)
<b>DIFFERENTIAL LOCK</b>		
Differential Lock		Electrical Switch Operated
<b>PTO</b>		
PTO (RPM)		540/540E 540/1000(optional)
PTO (Actuation)		Mechanical Operated Lever
<b>STEERING</b>		
Steering		Power
<b>ELECTRICAL</b>		
Battery		12V, 110Ah
Alternator		12V, 90A
Seven Pin Trailer Socket		Yes
<b>HYDRAULICS</b>		
Position & Draft Control		Electronic Lift (EHR)
3 Point Linkage		CAT-II
Lifting Capacity		4500 Kg
Auxillary Hydraulic Circuit		3DA , 2 SA convertible with 1 Detent

FEATURES		Sonalika 125 HP CABIN
<b>SAFETY SWITCH</b>		
Neutral Safety Switch		Standard
P.T.O Safety Switch		Standard
Clutch Safety Switch		Standard
<b>CAPACITY (LTRS)(+/-5%) APPROX</b>		
Fuel Tank (Ltr)		150
<b>TURNING RADIUS IN (m)</b>		
Without Brakes & With Brakes		6.2 (w/o brakes)
<b>TYRE</b>		
Tyres		Front: 380/85R24 Rear: 460/85R34
<b>DIMENSION &amp; WEIGHT (+/-5%)</b>		
Gross Weight (kg)		4665
Wheel Base (mm)		2645
Total Length (mm)		4660
Total Width (mm)		2260
Height (mm)		2660
Ground Clearance (mm) min		488
Front Track (mm)		1760
Rear Track (mm)		1724
<b>OTHERS</b>		
Fuel Indicator Gauge		Standard
Registration Plate with Light		Standard
Front Toe Hook		Standard
Front & Rear Weights		Front-31Kg*8+72Kg Base weight Rear-40*2Kg
Drawbar		Yes, Ladder Hitch
ROPS		Standard
Canopy		Standard
Cabin		Optional
<b>OPTIONAL FEATURES</b>		
Front Mudguard		Standard
Weight optional		Front- 31Kg*10

\*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

DEALER STAMP



**INTERNATIONAL TRACTORS LIMITED**

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)

Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221

Fax:+91- 01882-522222 | Email: exports@sonalika.com | URL: www.international.sonalika.com