

SONALIKA

HEAVY DUTY TRACTOR RANGE FOR YOUR FIELD

125



AGILE 6 CYLINDER
ENGINE

24F+24R SYNCHROMESH
TRANSMISSION

HEAVY LIFT
CAPACITY

SMART TECH
FEATURES

INTEGRATED SAFETY
HVAC CABIN (OPTIONAL)



**COST
EFFICIENT**
MECHANICAL TRACTORS

MADE OF
**REAL
STEEL**

STRATEGIC
COLLABORATION
WITH
YANMAR

HEAVY DUTY TRACTOR RANGE

FOR YOUR FIELD

125

SONALIKA



FEATURES		Sonalika 125 HP CANOPY
ENGINE		
HP Category		125 HP
No. of Cylinders		6
Displacement cc		6.127 L
Aspiration		Turbocharged with Intercooler
Bore/Stroke (mm)		105 x 118
Rated RPM		2200
Air Cleaner		Three stage dry type
Max Torque		475
TRANSMISSION		
Drive		4WD
Clutch		Double Clutch
Gearbox		24F+24R
Transmission		Synchromesh Gear Box
4WD Engagement		Electrical Switch Operated
SPEED (FORWARD)		
Min Speed (km/h)		0.67 Kmph
Max Speed (km/h)		40 Kmph
Driver Seat		Mechanical Suspension
BRAKES		
Brakes		Wet Disk Brakes
Type of Actuation		Hydraulic Actuated
Hand Brake		Mechanical, Hand operated
Trailer Brakes		HTB (Standard)
DIFFERENTIAL LOCK		
Differential Lock		Electrical Switch Operated
PTO		
PTO (RPM)		540/540E 540/1000(optional)
PTO (Actuation)		Mechanical Operated Lever
STEERING		
Steering		Power
ELECTRICAL		
Battery		12V, 110Ah
Alternator		12V, 90A
Seven Pin Trailer Socket		Yes
HYDRAULICS		
Position & Draft Control		Electronic Lift (EHR)
3 Point Linkage		CAT-II
Lifting Capacity		4500 Kg
Auxillary Hydraulic Circuit		3DA , 2 SA convertible with 1 Detent

FEATURES		Sonalika 125 HP CANOPY
SAFETY SWITCH		
Neutral Safety Switch		Standard
P.T.O Safety Switch		Standard
Clutch Safety Switch		Standard
CAPACITY (LTRS)(+/-5%) APPROX		
Fuel Tank (Ltr)		150
TURNING RADIUS IN (m)		
Without Brakes & With Brakes		6.2 (w/o brakes)
TYRE		
Tyres		Front: 380/85R24 Rear: 460/85R34
DIMENSION & WEIGHT (+/-5%)		
Gross Weight (kg)		4665
Wheel Base (mm)		2645
Total Length (mm)		4660
Total Width (mm)		2260
Height (mm)		2660
Ground Clearance (mm) min		488
Front Track (mm)		1760
Rear Track (mm)		1724
OTHERS		
Fuel Indicator Gauge		Standard
Registration Plate with Light		Standard
Front Toe Hook		Standard
Front & Rear Weights		Front-31Kg*8+72Kg Base weight Rear-40*2Kg
Drawbar		Yes, Ladder Hitch
ROPS		Standard
Canopy		Standard
Cabin		Optional
OPTIONAL FEATURES		
Front Mudguard		Standard
Weight optional		Front- 31Kg*10

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

DEALER STAMP



INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)

Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221

Fax:+91- 01882-522222 | Email: exports@sonalika.com | URL: www.international.sonalika.com